



OXY 70 | Portable OXY Meter

Electrochemistry on the Move
The Portable Solution

O₂ -

Barometric pressure - Temperature - GLP - Data Logger

Features



GLP functions:

Date and time, recall of calibration data and function "Calibration due."



Data logger up to 1000 datas, automatic and manual, PC connection via micro-USB



Automatic brightness regulation, for long battery life.

Available with

Description
Optical sensor , with temperature sensor integrated. Cable lenght: 2 meters
Optical sensor , with temperature sensor integrated. Cable lenght: 10 meters
Replacement membrane for Optical sensor
Polarographic sensor, with temperature sensor integrated, cable lenght 3 m, 2 replacement membranes, refi ll solution (30ml)
Kit of 2 replacement membranes for polarographic sensor
Refill solution for polarographic sensor



Only 6 buttons to easily manage all the functions of the instrument.

A comfortable portable laboratory. The instrument is supplied in a practical kit which includes:
0 Oxygen standard, replacement membrane, USB cable and power supply (70 Vio series only), user manual and plastic carrying case.



Datasheet

OXY 70	
O2 dissolved Measuring range	0,00...50,0 mg/l
Resolution	0.01 (< 20,00 mg/l) / 0.1 (> 20,0 mg/l)
Accuracy	± 0,2 < 10 mg/l-ppm ± 0,3 from 10 to 20 mg/l-ppm ± 5% > 20 mg/l-ppm
O2 saturation Measuring range	0,0...199,9 % / 200...400%
Resolution	0,1 / 1%
Accuracy	± 10%
Calibration point	1 or 2 automatic
Calibration point indication	Yes
Calibration report	Yes
Barometric pressure Measuring range	0...1100 mbar
Resolution	1 mbar
Accuracy	± 0,5%
Pressure automatic compensation	Yes
Temperature Measuring range	-10,0...110,0 °C
Resolution	± 0,1°C
Accuracy	± 0,5°C
Temperature compensation	Yes, only automatic
Salinity compensation	Yes, manual
System : GLP	Yes
Calibration due	Yes
Internal memory	1000 Data
Display	High definition backlit colour LCD
Brightness adjustment	Automatic
IP protection	IP 57
Output	Micro USB
Working conditions	T= 0 ... +45 °C / H = < 95 %
Power	3 batteries AA 1,5 V / Power supply 5 V
Dimensions / Weight	185 x 85 x 45 mm / 400 g

Visit Website



Connect with us
on LinkedIn



Service Support:

✉ lab.support@borosil.com
☎ 1800-224-551