



COND 70 | Portable Conductivity Meter

Electrochemistry on the Move
The Portable Solution

COND 70

Cond - TDS - Salinity - Temperature

Features



GLP functions:
Date and time, recall of calibration data and function "Calibration due".



Data logger up to 1000 datas, automatic and manual, PC connect via micro-USB



Automatic brightness regulation, for long battery life.

Accessories

Consumables provided

Optical sensor , with temperature sensor integrated.
Cable lenght: 2 meters

Optical sensor , with temperature sensor integrated.
Cable lenght: 10 meters

Replacement membrane for Optical sensor

Polarographic sensor, with temperature sensor integrated, cable lenght 3 m, 2 replacement membranes, refill solution (30ml)

Kit of 2 replacement membranes for polarographic sensor

Refill solution for polarographic sensor



Only 6 buttons to easily manage all the functions of the instrument.

A comfortable portable laboratory.

The instrument is supplied in a practical kit which includes:
0 Oxygen standard, replacement membrane, USB cable and power supply (70 Vioseries only), user manual and plastic carrying case.



Datasheet

COND 70

COND Measuring range	0,00 ... 200 mS
Resolution	0,01 - 0,1 - 1 μ S / mS (automatic)
Accuracy	\pm 2% f.s.
Calibration points	1...5 automatic + 1 custom
Recognized buffers	84 μ S - 147 μ S - 1413 μ S - 12,88 mS - 111,8 mS
Reference temperature	15 ... 30 $^{\circ}$ C
Temperature coefficient	Temperature coefficient 0,00 ... 10,00 % / $^{\circ}$ C
Buffer indication	Yes
TDS Measuring range	0,1 mg/l ... 200 g/l
TDS factor	0,40 ... 1.00
Salinity Measuring range	0,1 ppm ... 100 ppt
Temperature Measuring range	-10,0...110,0 $^{\circ}$ C
Resolution / Accuracy	0,1 / \pm 0,5 $^{\circ}$ C
Temperature compensation	0,0...100,0 $^{\circ}$ C
System : GLP	Yes
Calibration due	Yes
Buffer indication	Yes
Calibration report	Yes
Stability filter	Low – Nor - High
Internal memory	1000 Data
Display	High definition backlight colored LCD
Brightness adjustment	Automatic / Manual
IP protection	IP 57
Output	Micro USB
Power	3 batteries AA 1,5 V
Working conditions	T= 0 ... +45 $^{\circ}$ C / H = < 95 %
Dimensions / Weight	185 x 85 x 45 mm / 400 g

Visit Website



Connect with us
on LinkedIn



BOROSIL®
Scientific

1101, Crescenzo, G-Block, Opp. MCA Club,
Bandra Kurla Complex, Bandra (E), Mumbai - 400 051. India
T : +91 22 6740 6300 F : +91 22 6740 6514
E : borosil@borosil.com W : www.borosil.com

Pune Manufacturing Unit:
BOROSIL SCIENTIFIC LTD.
21-24, Plot No. 8, Indialand Global Industrial Park,
Hinjewadi Phase - 1, Pune - 411 057

Service Support:

✉ lab.support@borosil.com
☎ 1800-224-551